

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 March 2001 (08.03.2001)

PCT

(10) International Publication Number
WO 01/16614 A1

(51) International Patent Classification?: **G01R 31/36**

(21) International Application Number: **PCT/US00/24266**

(22) International Filing Date:
1 September 2000 (01.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/388,276 1 September 1999 (01.09.1999) US

(71) Applicant and

(72) Inventor: **CHAMPLIN, Keith, S.** [US/US]; 5437 Elliott Avenue South, Minneapolis, MN 55417 (US).

(74) Agents: **CHAMPLIN, Keith, S. et al.**; Westman, Champlin & Kelly, P.A., International Centre - Suite 1600, 900 Second Avenue South, Minneapolis, MN 55402-3319 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **METHOD AND APPARATUS FOR ELECTRONICALLY EVALUATING THE INTERNAL TEMPERATURE OF AN ELECTROCHEMICAL CELL OR BATTERY**



(57) Abstract: A testing device applies time-varying electrical excitation to a cell or battery (20) and senses the resulting time-varying electrical response. Computation circuitry (50) within the device uses voltage and current signals derived from the excitation and response signals as inputs and computes values of elements of an equivalent circuit representation of the cell or battery (20). The internal temperature of the cell or battery (20) is calculated from the value of the time constant of a particular parallel G-C subcircuit of the equivalent circuit. The battery's (20) internal temperature is then either displayed to the user, used to apply appropriate temperature corrections to other computed quantities, used to detect thermal runaway, and/or used to control an external process such as charging of the battery (20).

-1-

METHOD AND APPARATUS FOR ELECTRONICALLY
EVALUATING THE INTERNAL TEMPERATURE OF AN
ELECTROCHEMICAL CELL OR BATTERY

BACKGROUND OF THE INVENTION

5 The present invention relates to testing of storage batteries. More specifically, the invention relates to measuring temperature of an electrochemical cell or battery.

10 When testing or evaluating the performance of cells and batteries, it is desirable to accurately know battery temperature in order to apply appropriate temperature corrections to the measured results. For example Champlin, in U.S. Patent 3,909,708, describes setting a dial on the tester to the battery's
15 temperature in order to cause the measured dynamic conductance to comport with that of a battery at room temperature. However, exactly how this battery temperature information is to be obtained is not discussed. Others employ a very rough correction by
20 instructing the user to push a button when the ambient temperature is, e.g., "below 0° C". Marino et al., in U.S. Patent 4,423,378 refer to a battery temperature "probe" whose output is inputted to a microprocessor for the purpose of correcting load-test results.
25 Similar temperature probes are described by Alber et al. in U.S. Patent 4,707,795. Other workers have attached thermistors to test clips so that they would be in thermal contact with a battery terminal, or have

-2-

placed them in thermal contact with the battery's case. Even infrared techniques have been used to determine battery case temperature.

5 All of these prior art techniques have measured either the battery's ambient temperature or its external case temperature. Unfortunately however, these quantities can be very different from the actual internal temperature of the battery -- the truly desired quantity. These temperature differences come about from localized internal heating caused by
10 currents flowing through the battery, from the large thermal mass of the battery, and from the poor thermal contact between the battery and its environment. For example, an automobile engine compartment will warm up rapidly with the engine running. If the battery is
15 cold, however, its internal temperature will remain low for a very long period of time.

SUMMARY OF THE INVENTION

A testing device applies time-varying
20 electrical excitation to a cell or battery and senses the resulting time-varying electrical response. Computation circuitry within the device uses voltage and current signals derived from the excitation and response signals as inputs and computes values of
25 elements of an equivalent circuit representation of the cell or battery. The internal temperature of the cell or battery is calculated from the value of the time constant of a particular parallel G-C subcircuit of the equivalent circuit. In various aspects, the battery's

-3-

internal temperature is then displayed to the user, used to apply appropriate temperature corrections to other computed quantities, used to detect thermal runaway, and/or used to control an external process
5 such as charging of the battery.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a device for measuring the internal temperature of an electrochemical cell or battery according to the
10 present invention.

FIG. 2 depicts a six-element small signal equivalent circuit representation of a particular automotive storage battery.

FIG. 3 is a plot of the variation of the
15 three subcircuit time-constants defined in FIG. 2 as functions of the charge removed from the battery.

FIG. 4 is a plot of measured and theoretical values of time constant τ_3 defined in FIG. 2 as functions of the internal temperature of the battery.

20 FIG. 5 is a plot of the inverse of the relationship plotted in FIG. 4.

FIG. 6 is a circuit representation of the parallel G3-C3 subcircuit showing its admittance Y3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 Clearly, a method and apparatus for electronically determining the true internal temperature of a cell/battery would be of great value. The present invention addresses this need. It is based upon teachings disclosed in pending

-4-

A very important application of the method taught herein is in the detection of "thermal runaway" - a phenomenon in which the internal temperature of a battery undergoing charging rises catastrophically (see, e.g., McShane et al., U.S. Patent 5,574,355). Using the technique disclosed below, a runaway condition can be quickly detected by a precipitous internal temperature rise, which, in turn could be used to shut off the charger or reduce its charging voltage.

Figure 1 discloses a block diagram of apparatus for evaluating a battery's internal temperature according to the present invention. Apparatus of this type is fully disclosed in pending U.S. Patent Application Ser. No. 09/152,219, filed September 11, 1998 and entitled "METHOD AND APPARATUS FOR MEASURING COMPLEX IMPEDANCE OF CELLS AND BATTERIES" and pending U.S. Patent Application 09/151,324, filed September 11, 1998, entitled "METHOD AND APPARATUS FOR DETERMINING BATTERY PROPERTIES FROM COMPLEX IMPEDANCE ADMITTANCE" which are incorporated herein by reference. Measuring circuitry 10 electrically couples to cell/battery 20 by means of current-carrying contacts A and B and voltage-sensing contacts C and D. Measuring circuitry 10 passes a periodic time-varying current $i(t)$ through contacts A and B and senses a periodic time-varying voltage $v(t)$ across contacts C and D. By appropriately processing and combining $i(t)$ and $v(t)$, measuring circuitry 10 determines real and

-5-

imaginary parts of a complex parameter, either impedance Z or admittance Y , at a measuring frequency f_k ; where f_k is a discrete frequency contained in the periodic waveforms of both $i(t)$ and $v(t)$.

5 Control circuitry 30 couples to measuring circuitry 10 via command path 40 and commands measuring circuitry 10 to determine the complex parameter of cell/battery 20 at each one of n discrete measuring frequencies, where n is an integer
10 number. This action defines $3n$ experimental quantities: the values of the n measuring frequencies and the values of the n imaginary parts and n real parts of the complex parameter at the n measuring frequencies.

15 Computation circuitry 50 couples to measuring circuitry 10 and to control circuitry 30, via data paths 60 and 70, respectively, and accepts the $2n$ experimental values from measuring circuitry 10 and the values of the n measuring frequencies from
20 control circuitry 30. Upon a "Begin Computation" command from control circuitry 30 via command path 80, computation circuitry 50 uses algorithms disclosed in U. S. Patent Application 09/151,324 to combine these $3n$ quantities numerically to evaluate
25 $2n$ elements of an equivalent circuit representation of the cell/ battery. Computation circuitry 50 then calculates the internal temperature of the cell/battery from values of particular elements of this circuit representation. Finally, computation

-6-

circuitry 50 outputs the computed result to the user on display 90 and/or uses the result to activate an alarm 100 or to control a process 110 such as a battery charger.

5 In practice, a microprocessor or microcontroller running an appropriate software program can perform the functions of both control circuitry 30 and computation circuitry 50.

Figure 2 discloses a six-element equivalent
10 circuit representation of a typical automotive storage battery. This circuit representation was evaluated using apparatus of the type disclosed in FIG 1 with $n=3$ by employing algorithms disclosed in U.S. Patent Application 09/151,324. The three
15 measurement frequencies were 5 Hz, 70 Hz, and 1000 Hz. One notes that the $n=3$ equivalent circuit comprises three subcircuits:

- A series G1-L1 subcircuit.
- A parallel G2-C2 subcircuit.
- 20 • A parallel G3-C3 subcircuit.

One notes further that the three subcircuits are characterized by having very different time constants. The shortest time constant,
 $\tau_1 = L1 \cdot G1 = 93.5\mu S$, belongs to the series G1-L1
25 subcircuit. The next longest time constant,
 $\tau_2 = C2/G2 = 2.22mS$, belongs to the parallel G2-C2 subcircuit; and the longest time-constant,
 $\tau_3 = C3/G3 = 41.6mS$, belongs to the parallel G3-C3

-7-

subcircuit. Accordingly, the three subcircuits represent quite different physical processes and can be differentiated from one another by their time constants.

5 Figure 3 is a logarithmic plot of the three time constants defined above as functions of charge (ampere-hours) removed from the battery. One notes that the three time constants remain widely separated as charge is removed, and that the longest of the
10 three, τ_3 , is nearly independent of state-of-charge. This result is important to the present invention.

 Figure 4 discloses the observed variation of time constant $\tau_3 = C3/G3$ with internal battery temperature. One sees that τ_3 varies inversely with
15 temperature. This variation is consistent with a theoretical model that associates the G3-C3 subcircuit with a linearized, small-signal, representation of the nonlinear electrochemical reaction occurring at the negative plates. For such a model, the RC product
20 $\tau_3 = C3/G3$ represents the reaction time for the process and therefore varies inversely with temperature. By empirically establishing this relationship between τ_3 and T, one can actually utilize measurements of τ_3 to determine the battery's internal temperature, T.

25 Figure 4 shows experimental points compared with a theoretical $\tau_3(T_c)$ relationship. Note that the steepest slope, and hence the most accurate temperature determination, occurs in the most interesting region

- 8 -

between -20° C and $+20^{\circ}$ C. The theoretical curve disclosed in FIG. 4 is a plot of the following equation:

$$\tau_3(T_c) = K_3 + \frac{1}{\frac{1}{K_2} + \frac{1}{K_1 \exp\{qV_0/k(T_c + 273^{\circ})\}}} \quad (1)$$

where τ_3 is the time constant measured in milliseconds and T_c is the internal temperature measured in degrees Celsius. Physical parameters introduced in this equation are:

$k = 1.38 \times 10^{-23}$ Joules/ $^{\circ}$ K (Boltzman's Constant)

$q = 1.6 \times 10^{-19}$ Coulombs (electronic charge)

$V_0 = 0.85$ eV (activation energy)

The three constants K_1 , K_2 , and K_3 were empirically determined to be

$$K_1 = 2.0 \times 10^{-14}$$

$$K_2 = 67.0 \text{ mS}$$

$$K_3 = 37.0 \text{ mS}$$

One notes excellent agreement between theory and experiment. Measurements show that τ_3 is virtually independent of battery size and state-of-charge (see FIG. 3). Thus, this empirical $\tau_3(T_c)$ relationship plotted in FIG. 4 appears to be quite universal.

In order to determine internal temperature from time constant measurements, one must

-9-

mathematically invert the above $\tau_3(T_c)$ relationship to obtain a $T_c(\tau_3)$ relationship. The result is:

$$T_c(\tau_3) = \frac{(qV_0/k)}{\ln \left\{ \frac{(K_2/K_1)(\tau_3 - K_3)}{(K_2 + K_3 - \tau_3)} \right\}} - 273^\circ \quad (2)$$

5

where the parameters and constants, q , V_0 , k , K_1 , K_2 , K_3 , are the same as those introduced in the $\tau_3(T_c)$ relationship.

The inverse theoretical $T_c(\tau_3)$ curve is plotted in FIG. 5. By employing this relationship, one can readily determine the battery's true internal temperature from measurements of τ_3 . This important temperature information can then be used to apply accurate temperature corrections to other measured quantities, such as CCA, state-of-charge, and amp-hour capacity. It can also be used to detect a thermal runaway condition, and to control an external process such as a battery charger.

This completes the disclosure of my invention. Figures 6, however, will place the true nature of the invention in greater perspective. Figure 6 illustrates the G3-C3 subcircuit and shows that the complex admittance of this parallel subcircuit, $Y3 = G3 + j\omega C3$, explicitly contains the two quantities, $G3$ and $C3$, necessary to determine the battery's internal temperature. Thus, my discussion above actually discloses a relationship existing between the

-10-

real and imaginary parts of Y_3 and the internal temperature of the battery. Although it is true that complex Z and complex Y are reciprocals of one another, no simple relationship exists between the real and imaginary parts of impedance Z_3 and time constant τ_3 .
5 Accordingly, the results of any ac measurement must be expressed in complex admittance form - not complex impedance form - in order to observe the important relationship that I have disclosed herein. How this
10 complex admittance is obtained, however, is relatively unimportant.

Although my disclosure has relied upon particular apparatus and algorithms previously disclosed in U.S. Patent Applications Ser. No.
15 09/152,219 and Ser. No. 09/151,324, other methods will be apparent to one skilled in the arts. For example, one can employ bridges or other types of apparatus to measure complex admittance (or its reciprocal, complex impedance). Furthermore, if accuracy is not a strict
20 requirement, one can take advantage of the fact that the various time constants are widely separated from one another and simply assume that the subcircuits are not coupled. Within this approximation, C_2 and C_3 are treated as short circuits at frequencies near
25 $f_{01} = 1/2\pi\tau_1$, L_1 and C_3 are treated as short circuits at frequencies near $f_{02} = 1/2\pi\tau_2$, and at frequencies near $f_{03} = 1/2\pi\tau_3$, L_1 is treated as a short circuit while C_2 is treated as an open circuit. Thus, with some batteries,

-11-

it is possible to obtain satisfactory results from a very simple analysis of measurements at two or three frequencies. With certain batteries, it is even possible to obtain useful approximations to Y^3 from
5 measurements of complex Y or $Z = 1/Y$ obtained at a single, appropriately chosen, frequency. Workers skilled in the art will recognize that these and other variations may be made in form and detail without departing from the true spirit and scope of my
10 invention.

-12-

WHAT IS CLAIMED IS:

1. Apparatus for determining the internal temperature of an electrochemical cell or battery comprising:
electrical excitation circuitry adapted to apply time-varying electrical excitation to said cell or battery;
response sensing circuitry configured to sense time-varying electrical response of said cell or battery generated as a result of said time-varying electrical excitation; and
computation circuitry responsive to said time-varying excitation and to said time-varying response and adapted to calculate the time constant of a particular parallel G-C subcircuit comprising part of an electrical circuit representation of said cell or battery, said time constant characterized by varying inversely with internal temperature, said computation circuitry further adapted to evaluate said internal temperature from the computed value of said time constant.

-13-

2. The apparatus of claim 1 including a display device coupled to said computation circuitry and wherein the computation circuitry provides a temperature output on the display.
3. The apparatus of claim 1 wherein said computation circuitry couples to an external process device and said external process device is controlled by said computation circuitry in accordance with the computed value of said internal temperature.
4. The apparatus of claim 1 wherein said electrical circuit representation comprises at least three subcircuits having differing time constants and the time constant of said particular parallel subcircuit is longer than the time constants of at least two other subcircuits.
5. The apparatus of claim 1 wherein said electrical circuit representation comprises at least two subcircuits having different time constants and the time constant of said particular parallel subcircuit is longer than the time constant of at least one other subcircuit.
6. The apparatus of claim 1 including an output indicative of detect a thermal runaway condition, said condition characterized by a rapid rise in internal temperature while charging of the battery.
7. The apparatus of claim 6 including an alarm coupled to said computation circuitry and wherein the

-14-

computation circuitry provides an alarm output in response to said thermal runaway condition.

8. The apparatus of claim 3 wherein said external process device is a battery charger.

9. A method for electronically evaluating the internal temperature an electrochemical cell or battery comprising:

applying time-varying electrical excitation to said cell or battery;

sensing time-varying electrical response to said electrical excitation;

evaluating the time constant of a particular parallel G-C subcircuit of an equivalent circuit representation of said cell or battery from said time-varying electrical excitation and said time-varying electrical response; and

evaluating said internal temperature from the value of said time constant.

10. The method of claim 9 including the displaying said internal temperature to a user.

-15-

11. The method of claim 9 including the controlling an external process device in accordance with said internal temperature.









Fig. 3**Fig. 4****Fig. 5****Fig. 6**

INTERNATIONAL SEARCH REPORT

Intern: al Application No

PCT/US 00/24266

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G01R31/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 009, no. 085 (E-308), 13 April 1985 (1985-04-13) & JP 59 215674 A (SANYO DENKI KK), 5 December 1984 (1984-12-05) abstract	1,9
A	US 5 574 355 A (MC SHANE STEPHEN J ET AL) 12 November 1996 (1996-11-12) column 2, line 59 -column 5, line 6; figures 1,2	1,9

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

19 December 2000

Date of mailing of the international search report

29/12/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hijazi, A

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/24266

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 59215674	A	05-12-1984	NONE	
US 5574355	A	12-11-1996	AU 5363496 A WO 9629773 A	08-10-1996 26-09-1996